BIOSYMPH LIMITED

MATERIAL SAFETY DATA SHEET

Section 1. Identification of the material and the supplier

Product: ClimoPlate™ Product Code: CP - xxx

Product Use:

New Zealand Supplier:

Address:

Roof Paint Top Coat

Biosymph Limited

2287 Kakaramea Road

RD10 Whatawhata 3290

Hamilton

Telephone: +64 (0)7 829 8606 or +64 (0)22 607 6400 (mob)

eMail: admin@biosymph.co.nz

Emergency Telephone: 0800 76 47 66 (National Poisons Centre)

Date of MSDS Preparation: 23 January 2018 version 2

Section 2. Hazards Identification

This substance is not classified as a dangerous good according to NZS5433: 2007

Pictograms

NONE REQUIRED

HSNO Classification	Hazard Code	Hazard Statement
6.1E	H333	May be harmful if inhaled
6.3B	H316	Causes mild skin irritation
0.40	11444	Taria ta annatia life mitta langu lagting a f

9.1B H411 Toxic to aquatic life with long lasting effects

Prevention Code	Prevention Statement
P102	Keep out of reach of children
P103	Read label or visit our website www.biosymph.co.nz before use
P210	Keep away from heat and flames
P233	Keep container tightly closed
P273	Avoid release to the aquatic environment
P280	Wear protective gloves / eve protection

Response Code Response Statement

P303+361+353 IF ON SKIN: Remove all contaminated clothing immediately. Rinse skin with water

P370+378 In case of fire: Use foam, CO2 or dry powder

P304+312 IF INHALED: Call the POISON CENTRE or a doctor

P332+313 If skin irritation occurs: Get medical advice

P391 Collect spillage

Storage Code Storage Statement

P403+233 Store in a well-ventilated place. Keep container tightly closed.

Disposal Code Disposal Statement

P501 Crush or puncture container to prevent further use if not recycled. Dispose of

at an approved waste disposal site

Product Name: ClimoPlate™ Prepared by: Biosymph Ltd
Date of MSDS_v2: 23 January 2018 Tel: 64 7 829 8606 Website: www.biosymph.co.nz

Ingredients	Wt%	CAS NUMBER.
Mixed emulsified petroleum solvents in Water	40-80	Not available
Drying oils	10-20	Not available
Cut-back bitumen	1-15	8052-42-4

Section 4. First Aid Measures

Recommended on site emergency facilities: Eye wash station

Routes of Exposure:

If in Eyes Remove excess contamination around eyes with olive oil. Wash eyes with a

gentle stream of water to dislodge solid particles. Seek medical attention.

If on Skin Remove contaminated clothing. Physically scrape off excess and use olive oil

to dissolve residues. Finally wash skin or hair with soap and water.

If Swallowed DO NOT INDUCE VOMITING. Seek immediate medical attention.

If Inhaled Remove patient from contaminated area to fresh air. If patient does not

recover normal breathing and is distressed, seek medical advice.

Hazard Type	NON-flammable liquid
Hazards from decomposition products	Carbon dioxide, nitrogen oxides, unburnt hydrocarbons
Suitable Extinguishing media	Not Applicable

Section 6. Accidental Release Measures

Land Spill or Leaks

Small leaks or spills may be mixed with dry zeolite absorbent (kitty litter), sand or

soil and swept up for domestic rubbish disposal. Large spills, evacuate all unnecessary personnel.

Dyke the spill with appropriate spill media (zolite, sand or soil) and shovel into

recovery drums.

If the spill enters any waterway, sewer or stormwater notify the Environmental

Response unit at the nearest council offices.

Section 7. Handling and Storage

Approved Handlers: Not required.

Precautions for safe handling: Open containers cautiously as they may be under pressure. DO NOT store

in confined spaces.

Conditions for safe storage: Store in a cool, dry, well-ventilated area away from food, animal feedstuffs,

strong acids, alkalis and oxidizers. Protect from physical damage.

Regularly inspect bulk containers for leaks or cracks.

Page 3

Section 8 Exposure Controls / Personal Protection

WORKPLACE EXPOSURE STANDARDS (provided for guidance only)

TWA STEL Substance CAS# ppm mg/m3 ppm mg/m3

Asphalt

Workplace Exposure Standard – Time Weighted Average (WES-TWA). The time-weighted average exposure standard designed to protect the worker from the effects of long-term exposure. Workplace Exposure Standard – Short-Term Exposure Limit (WESSTEL). The 15-minute average exposure standard. Applies to any 15- Minute period in the working day and is designed to protect the worker against adverse effects of irritation, chronic or irreversible tissue change, or narcosis that may increase the likelihood of accidents. The WES-STEL is not an alternative to the WES-TWA; both the short-term and time-weighted average exposures apply.

Engineering Controls: Always provide good ventilation to keep vapours below the lower explosion limit

Personal Protective Equipment: Always wear suitable protective gloves (nitrile) and eye protection. In confined spaces, an organic vapour respiratory cartridge mask must be

used.

General: When large quantities are used, a plastic apron and rubber boots are recommended.

Section 9 Physical and Chemical Properties

Physical State: coloured liquid

Odour: petroleum bitumen odour

pH: not applicable

Solubility: soluble in organic solvents; partly soluble in water

Relative Vapour Density (air=1):

Boiling point:
Ignition Point:
Flash Point:
Specific Gravity:
Vapour Pressure:
Volatiles:

not available
initial 100°C
not available
not applicable
less than 1.2
2.13 kPa
10%

Evaporation Rate: not available

Section 10. Stability and Reactivity

Chemical Stability Stable under normal conditions. Does not polymerise

Conditions to Avoid Heat, direct sunlight, open flames

Incompatibility Strong oxidizers, acids, alkalis

Hazardous Decomposition

Products Fumes of nitrogen, carbon oxides and acrid unburnt hydrocarbons

Section 11 Toxicological Information

Acute Oral Toxicity LD₅₀ Rat (oral) 2000-5000 mg / kg bw

Acute Dermal Toxicity LD₅₀ Rat (dermal) 2000-5000 mg / kg bw

Chronic Effects Inhalation of vapours will irritate respiratory system. Prolonged skin

exposure will cause redness followed by dermatitis.

Product Name: ClimoPlate™ Prepared by: Biosymph Ltd
Date of MSDS_v2: 23 January 2018 Tel: 64 7 829 8606 Website: www.biosymph.co.nz

Section 12. Ecotoxicological Information

Environmental Precautions: Prevent from entering waterways or contaminating groundwater

Ecotoxicity Data: Not available

Environmental Fate: Persistent and non-biodegradable

Environmental Exposure Limits: Not set

Section 13. Disposal Considerations

Dispose of in approved hazardous landfills or by incineration.

Section 14 Transport Information

Classified as a NON-Dangerous Good for transport.

Section 15 Regulatory Information

HSNO Controls:

Tracking: Not required Approved Handlers: Not required

Location Test Certificate: 500 L in containers ≥ 5L; 1500 L in containers <5L; 250 L open

Hazchem signage: 1000 L Emergency Response Plan: 10,000 L

Section 16 Other Information

- 1. This product may not be used as a marine anti-fouling paint, for pruning wounds on trees or shrubs or in the commercial treatment of timber.
- 2. Hazardous Substances Data Bank (HSDB), a database of the National Library of Medicine's TOXNET system (http://toxnet.nlm.nih.gov).
- 3. Preparation of Safety Data Sheets, January 2018.

Abbreviations:

CAS No Chemical Abstracts Number

EPA Environmental Protection Authority

HSNO Hazardous Substances and New Organisms

NZIoC New Zealand Inventory of Chemicals

STEL Short Term Exposure Limit
TWA Time Weighted Average
WES Workplace Exposure Standard

References:

Supplier Material Safety Data Sheets EPA website: www.epa.govt.nz

Hazardous Substances Data Bank (HSDB), a database of the National Library of Medicine's TOXNET system

(http://toxnet.nlm.nih.gov).

Disclaimer:

This document has been compiled by Biosymph Limited and serves as the manufacturer's Material Safety Data Sheet ('MSDS'). It is based on information concerning the product which has been provided from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. The information sourced for the preparation of this document was correct and complete at the time of writing to the best of the writer's knowledge. The document represents the commitment to the company's responsibilities surrounding the supply of this product, undertaken in good faith. While Biosymph Ltd has taken all due care to include accurate and up-to-date information in this MSDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, Biosymph Ltd accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this MSDS. The information herein is given in good faith, but no warranty, express or implied is made.

This document should be taken as a safety guide for the product and its recommended uses, but is in no way an absolute authority.

Please consult the relevant legislation and regulations governing the use and storage of this type of product.

For further information, please contact Biosymph Ltd.

Issue Date: 16 October 2017

Revision Date: 23 January 2018 – Minor amendments made to template

Review Date: 23 January 2023